

PRESTANDEDEKLARATION

Nr CPR2024-10-14P

Svensk översättning. Tillhandahålls tillsammans med originalet, som bifogas på nästa sida.

1. Produkttypens unika identifikationskod

Målade hårda träfiberskivor (vita), teknisk klass HB (tjocklek: 3,2 mm).

2. Typ-, parti- eller serienummer eller annan uppgift som möjliggör identifiering av byggprodukten enligt CPR artikel 11.4

Träfiberskivor. Specifikationer. Del 2: Krav för hårda träfiberskivor. Uppfyller kraven i standarden LST EN 622-2.

3. Byggprodukts avsedda användning enligt tillämplig harmoniserad teknisk specifikation, såsom förutsedd av tillverkaren

Hårda träfiberskivor för användning som icke bärande element under torra förhållanden.

4. Tillverkarens namn, registrerade firma eller varumärke och kontaktadress enligt artikel 11.5

UAB "Grigeo Baltwood"

Vilniaus g. 10, Grigiškės, LT-27101 Vilnius

Litauen

5. I förekommande fall namn och kontaktadress till den auktoriserade representant vars mandat omfattar uppgifterna enligt artikel 12.2

Ej tillämpligt.

6. System för bedömning och fortlöpande kontroll av byggprodukts prestanda

System 2+

7. För prestandadeklaration avseende en byggprodukt som omfattas av en harmoniserad standard

EN 622-2:2005

8. Angiven prestanda

Väsentlig egenskap	Prestanda	Harmoniserad teknisk specifikation
Densitet	$\geq 900 \text{ kg/m}^3$	EN 622:2005
Tjocklekstolerans	$\pm 0,3 \text{ mm}$	EN 622:2005
Böjhållfasthet	$> 30 \text{ N/mm}^2$	EN 622:2005
Draghållfasthet vinkelrätt mot skivans plan	$> 0,5 \text{ N/mm}^2$	EN 622:2005
Tjocklekssvällning i vatten efter 24 timmar	$< 37 \%$	EN 622:2005
Fuktkvot	4-9 %	EN 622:2005
Bestämning av formaldehyd	$\leq 2 \text{ mg/100g}$	EN ISO 717-1, EN 622-1

9. Försäkran och undertecknande

Prestandan för den produkt som identifieras i punkterna 1 och 2 överensstämmer med den angivna prestandan i punkt 7. Denna prestandadeklaration har utfärdats på eget ansvar av den tillverkare som anges i punkt 4.

Undertecknat för tillverkaren av:

Artūras Dargis, processtekniker

Ort och datum för utfärdande: Vilnius, 14 oktober 2024

Underskrift: se det bifogade originalet.

UAB „Grigeo Baltwood“ • Vilniaus g. 10, Grigiškės, LT-27101, Vilnius kommun

Registreringsnummer: 126199731, register över juridiska personer

Tel.: +370 5 243 5900 • baltwood@grigeo.com • www.grigeo.com

Momsregistreringsnummer: LT261997314

OP Corporate Bank plc, filial i Litauen • Bankkod: 21500 • BIC (SWIFT): OKOYLT2X

Kontonummer: LT04 2150 0510 0007 1790

DECLARATION OF PERFORMANCE

No. CPR2024-10-14P

1. Unique identification code of the product-type:

Painted Hardboards (white), technical class HB (thickness – 3,2 mm)

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

Fiberboards. Specifications. Part 2: Requirements for hardboards, meets the requirements of standard LST EN 622-2.

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

Hardboards for use as a non-structural elements in dry conditions.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

***UAB "Grigeo Baltwood"
Vilniaus g.10, Grigiškės, LT – 27101 Vilnius
Lithuania***

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

Not applicable

6. System or systems of assessment and verification of constancy of performance of construction product:

System 2+

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

EN 622-2:2005

8. Declared performance:

<i>Essential characteristics</i>	<i>Performance</i>	<i>Harmonized technical specification</i>
<i>Density</i>	$\geq 900 \text{ Kg/m}^3$	<i>EN 622 :2005</i>
<i>Thickness tolerance</i>	$\pm 0,3 \text{ mm}$	
<i>Bending strength</i>	$> 30 \text{ N/mm}^2$	
<i>Inside adhesion</i>	$> 0,5 \text{ N/mm}^2$	
<i>Water swelling in 24h</i>	$< 37\%$	
<i>Humidity</i>	$4-9\%$	<i>EN ISO 717-1, EN 622-1</i>
<i>Determination of formaldehyde</i>	$\leq 2 \text{ mg/100g}$	

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Engineer Technologist Artūras Dargis

Vilnius 2024-10-14

(name and function)

(place and date of issue)

(signature)